



# Set-Up and Anchoring Tools

## ▼ Hydraulic Jacks ▼



◀ **10112**  
Norco  
12 Ton/  
Low-  
(Height  
6 11/16"  
to 13 3/16")



◀ **10113**  
Norco  
12 Ton/  
Standard-  
(Height  
9 7/16" to  
18 7/8 ")



◀ **10121**  
Norco 20  
Ton/  
Standard-  
(Height  
10 13/16" to 20  
3/16")



◀ **10113-A/H**  
12 Ton Air/  
Hydraulic Jack  
(Height 9.625" to 19.75")  
\*One year warranty-  
reduces lifting time- push  
button air valve- longer  
wear life- highly portable-  
versatile in mobile home  
set-up operations.



▲ **10050**- Electric Anchor Auger Drive Machine  
(20 RPM/ 120 V/ 1/2 HP) \*Bars and **10051** Adapter included.



◀ **10051**  
Anchor Drive  
Adapter for  
#**10050**  
Machine



◀ **10051-EYE**  
Eye Anchor  
Drive Adapter  
for #**10050**  
Machine

## Double Wide Roller Systems

Special Order Only- Complete roller systems include two flattop sections, specify 3 or 5 rollers, and one ring top for hitch jack. Track not provided. (We recommend heavy gauge channel iron or aluminum for track.) Rollers are 2" x 5/16" machined seamless tubing with press fitted bearings. No need to grease or oil...ever! Flanges are 1/2" steel- Top plates are 1/2" steel.



◀ **10500**- Complete  
3-point 3 Roller Set  
(Loads up to 27,000#)



▶ **10501**- Complete  
3-point 5 Roller Set ▶  
(Loads up to 50,000#)



▲ **10500-FL**  
3 Roller Flat  
Section Only



▲ **10500-RI**  
Ring Top  
Section Only



▲ **10501-FL**  
5 Roller Flat  
Section Only

Set-Up/  
Transport



◀ **10009** - Anchor  
Speed Wrench  
\*Simplifies anchor  
installation- allows for one-  
handed operation- for  
installing frame ties and  
tension head bolts- 15/16"  
socket on one side and a  
15/16" nut on the other- for  
use with ratchet combined  
with 15/16" socket.

